



5	1g	O-LUBE	PARKER O-LUBE
4	1	-015 V90	O-RING, -015 VITON 90A
3	1	-015 B/U	BACK-UP RING, -015 TEFLON
2	12	EE20 WIRE	20AWG TYPE EE TEFLON, COLORS
1	13g	PAVESEAL200	EPOXY, HI-TEMP
ITEM	QTY	PART NUMBER	DESCRIPTION

**NOTES:**

1. LEAK TEST WITH N2+ HYDRAULIC FLUID TO 660 BAR (10,000 PSI) FOR 1 MINUTE.
2. ELECTRICAL TEST @630VDC FOR 500 MEGOHMS FOR .01S ALL WIRES & LEAK PORT.
3. CUSTOMER REQUIREMENTS ARE FOR ONLY 11 WIRES TO PASS NOTES 1& 2.  
EXTRA WIRE MAY BE PROVIDED BY PAVE OR CUTOFF BY PAVE.

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5  
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005  
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS


 2751 Thunderhawk Court  
 Dayton, Ohio 45414-3445  
 U.S.A.  
 (937)890-1100  
 fax (937)890-5165  
[www.pavetechnologyco.com](http://www.pavetechnologyco.com)

DESCRIPTION

**SP11 W/11 EE#20 PAVE-SEAL**

PART NUMBER

**0375**

PROJECTION

