



NOTES:

1. LEAK TEST FOR 1210: 5000 PSI, HEX SIDE, NO BUBBLES 1 MINUTE MINIMUM.
LEAK TEST FOR 1210-1: 80 PSI, THREAD SIDE, NO BUBBLES 2 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MΩ .01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRES ARE NOT REQUIRED TO BEND SHARPLY AT EPOXY SEAL SURFACE.
6. NO VOIDS LARGER THAN $\phi.035$ [.89] ARE ACCEPTABLE.
7. DIMENSIONS ARE IN INCHES [millimeters].

11	2	E24 YELLOW	WIRE 24E MIL-W-16878/4 7/#32
10	2	E24 RED	WIRE 24E MIL-W-16878/4 7/#32
9	2	E24 ORANGE	WIRE 24E MIL-W-16878/4 7/#32
8	2	E24 GREEN	WIRE 24E MIL-W-16878/4 7/#32
7	2	E24 BROWN	WIRE 24E MIL-W-16878/4 7/#32
6	2	E24 BLUE	WIRE 24E MIL-W-16878/4 7/#32
5	2	E24 BLACK	WIRE 24E MIL-W-16878/4 7/#32
4	1	-908 VITON	O-RING -908 VITON 75
3	1	PARKER O-LUBE	LUBRICANT O-RING BARIUM-BASED
2	1	PAVE-Seal 200	EPOXY BLACK
1	1	1238	HOUSING SO12SR-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

PAVE technology co.

DESCRIPTION PAVE-Seal Cable Harnesses
SO12SR-SS-14-TE24-2-36 LO PROF

PART NUMBER *SEE NOTE 1
1210*

REVISION LEVEL F

PROJECTION