


1357	-012 FLUORO	O-RING -012 FLUOROSILICONE 70
1357-1	M83461/1-012	O-RING 2-012 BUNA 75
PN	ITEM 3 PART#	DESCRIPTION

14	1@49	EE24 PTFE YELL	WIRE 24 PTFE M22759/11-24
13	1@49	EE24 PTFE WHT	WIRE 24 PTFE M22759/11-24
12	1@49	EE24 PTFE VIO	WIRE 24 PTFE M22759/11-24
11	1@49	EE24 PTFE RED	WIRE 24 PTFE M22759/11-24
10	1@49	EE24 PTFE ORG	WIRE 24 PTFE M22759/11-24
9	1@49	EE24 PTFE GRN	WIRE 24 PTFE M22759/11-24
8	1@49	EE24 PTFE GRAY	WIRE 24 PTFE M22759/11-24
7	1@49	EE24 PTFE BLUE	WIRE 24 PTFE M22759/11-24
6	1@49	EE24 PTFE BLK	WIRE 24 PTFE M22759/11-24
5	1	RR N5000-56	RETAINING RING INTERNAL 0.562
4	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM BASED
3	1	SEE ABOVE TABLE	SEE ABOVE TABLE
2	A/R	PAVE-Seal 200	EPOXY BLACK HI-TEMP
1	1	1226 SP8S	HOUSING SP8S-E
ITEM	QTY	PART#	DESCRIPTION

**NOTES:**

- 5 SHOCK CYCLES: -60°C TO 71°C 0.5 HOUR HOLD @ TEMP & 5 MINUTE MAXIMUM TRANSFER TIME.
- LEAK TEST: 80 PSI, NO BUBBLES 2 MINUTES MINIMUM.
- HYPOT 630 VDC 500 MW 0.01 SEC MINIMUM, WIRE TO WIRE & SHIELDS WHEN TESTED IN ACCORDANCE WITH MIL-STD-202, METHOD 302.
- ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
- PERCENTAGE OF PARTS TESTED WILL BE 100% (MAY BE A LESSER PERCENTAGE FOR LARGE PRODUCTION QUANTITIES, UNLESS OTHERWISE NOTED OR REQUIRED).
- NO O-RING LUBRICANT IS TO BE USED ON 1357-1.

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5  
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005  
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS


 2751 Thunderhawk Court  
 Dayton, Ohio 45414-3445  
 U.S.A.  
 (937)890-1100  
 fax (937)890-5165  
 www.pavetechnologyco.com

DESCRIPTION: PAVE-Seal® Cable Harnesses  
**SP8S-E-200-9-TEE24-24**

PART NUMBER: **1357**

REVISION LEVEL: **C**

PROJECTION: 