



1358	-016 FLUORO	O-RING -016 FLUOROSILICONE 70
1358-1	M83461/1-016	O-RING 2-016 BUNA 75
PN	ITEM 2 PART#	DESCRIPTION

- NOTES:**
- 5 SHOCK CYCLES: -60°C TO 71°C 0.5 HOUR HOLD @ TEMP & 5 MINUTE MAXIMUM TRANSFER TIME.
 - LEAK TEST: 80 PSI, NO BUBBLES 2 MINUTES MINIMUM.
 - HYPOT 630 VDC 500 MW 0.01 SEC MINIMUM, WIRE TO WIRE WHEN TESTED IN ACCORDANCE WITH MIL-STD-202, METHOD 302.
 - ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
 - PERCENTAGE OF PARTS TESTED WILL BE 100% (MAY BE A LESSER PERCENTAGE FOR LARGE PRODUCTION QUANTITIES, UNLESS OTHERWISE NOTED OR REQUIRED).
 - NO O-RING LUBRICANT IS TO BE USED ON 1358-1.

9	37.16	EE12 PTFE BLK	WIRE 12PTFE M22759/11-12
8	37.16	EE12 PTFE BRN	WIRE 12PTFE M22759/11-12
7	37.16	EE12 PTFE GRN	WIRE 12PTFE M22759/11-12
6	37.16	EE12 PTFE WHT	WIRE 12PTFE M22759/11-12
5	1	RR 5100-75-HST	RETAINING RING EXTERNAL .750SS
4	A/R	PAVE-Seal 150	EPOXY BLACK
3	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM BASED
2	1	SEE ABOVE CHART	SEE ABOVE CHART
1	1	0130 SPF12	HOUSING SPF12-E
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION *PAVE-Seal® Cable Harnesses*
SPF12-E-150-4-TEE12-18-18

PART NUMBER **1358**

REVISION LEVEL **C**

PROJECTION