



PART #	X	Y	Z
1408	4	4	9
1408-1	24	10	35

NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 2.5 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MW 0.01 SEC MINIMUM, WIRE TO WIRE.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. REF-RETAINING RING: WALDES TRUARC 5103-75 OR EQUAL (NOT INCLUDED).
5. REF-.003" MAX FLASH AT PARTING LINE.

9	Z"	EE18 MIL ORANGE	WIRE 18EE MIL-W-16878/5 .015 7/#26
8	Z"	EE18 MIL WHITE	WIRE 18EE MIL-W-16878/5 .015 7/#26
7	Z"	EE18 MIL RED	WIRE 18EE MIL-W-16878/5 .015 7/#26
6	Z"	EE18 MIL GRN	WIRE 18EE MIL-W-16878/5 .015 7/#26
5	Z"	EE18 MIL BROWN	WIRE 18EE MIL-W-16878/5 .015 7/#26
4	Z"	EE18 MIL BLK	WIRE 18EE MIL-W-16878/5 .015 7/#26
3	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM-BASED
2	1	-016 BUNA	O-RING -016 BUNA 70
1	1	0130	HOUSING SPF12-E
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



DESCRIPTION PAVE-Seal® Cable Harnesses
 SPF12-E-150-6-TEE18-X-Y SEE TABLE

PART NUMBER 1408 PROJECTION