



NOTES:

1. THE LEAK TEST @ 1 ATM. 10^{-6} CC/S AIR EQUIVALENT. (AIR EQUIVALENT LEAK RATE/2.73 = ACTUAL He LEAK RATE)
2. HYPOT 630 VDC 500 MEGOHMS .01 SEC MINIMUM, WIRE TO WIRE.
3. ALL TESTS ARE DONE AT ROOM TEMPERATURE.
4. THESE SPECIFICATIONS SUPERSEDE PAVE CATALOG.
5. REF-OPERATING RANGE -200°C TO 200°C.
6. PACKAGING REQUIRED WHICH WILL AFFORD ADEQUATE PROTECTION AGAINST PHYSICAL DAMAGE DURING HANDLING, SHIPMENT, & STORAGE.
7. WIRE PAIRS: BROWN & GREEN, RED & BLUE, ORANGE & VIOLET, AND YELLOW & GRAY.

11	A/R	SUPER O-LUBE	LUBRICANT O-RING SILICONE
10	1	-010 VITON	O-RING -010 VITON 75A
9	1	0168	HOUSING SP6-E
8	1@34"	E28 SOLID YELLOW	WIRE 28E SOLID SILVER PLATED COPPER
7	1@34"	E28 SOLID VIOLET	WIRE 28E SOLID SILVER PLATED COPPER
6	1@34"	E28 SOLID RED	WIRE 28E SOLID SILVER PLATED COPPER
5	1@34"	E28 SOLID ORANG	WIRE 28E SOLID SILVER PLATED COPPER
4	1@34"	E28 SOLID GREEN	WIRE 28E SOLID SILVER PLATED COPPER
3	1@34"	E28 SOLID GRAY	WIRE 28E SOLID SILVER PLATED COPPER
2	1@34"	E28 SOLID BROWN	WIRE 28E SOLID SILVER PLATED COPPER
1	1@34"	E28 SOLID BLUE	WIRE 28E SOLID SILVER PLATED COPPER
ITEM	QTY	ITEM NUMBER	ITEM DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION **PAVE-Seal® Cable Harnesses**
SP6-E-200-4TP-TE28-6-24
 PART NUMBER **1413**
 PROJECTION