


NOTES:

1. LEAK TEST FOR 1522: 4000 PSI, NO BUBBLES 2 MINUTES MINIMUM.
2. LEAK TEST FOR 1522-1: 5000 PSI, NO BUBBLES 2 MINUTES MINIMUM.
3. HYPOT 630 VDC 500 MΩ 0.01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
4. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
5. WIRES ARE NOT REQUIRED TO BEND SHARPLY AT EPOXY SEAL SURFACE.
6. DIMENSIONS IN INCHES [mm].
7. REF- TEMPERATURE RANGE OF USE: -20 TO 125°C.

| | | | |
|------|-----|---------------|---------------------------------|
| 5 | A/R | SUPER O-LUBE | O-RING LUBRICANT SILICONE BASED |
| 4 | 1 | -905 VITON | O-RING -905 VITON 75 |
| 3 | A/R | PAVE-Seal 150 | EPOXY BLACK |
| 2 | 8 | EE24 PTFE WHT | WIRE 24PTFE M22759/11-24 |
| 1 | 1 | 2074 | HOUSING S08-SS |
| ITEM | QTY | PART # | DESCRIPTION |


 2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

| | | |
|-------------|---------------------------|----------------|
| DESCRIPTION | PAVE-Seal Cable Harnesses | |
| | S08-SS-150-8-TE24-24-24 | |
| PART NUMBER | 1522 | REVISION LEVEL |
| | | D |
| | | PROJECTION |
| | | ☉ ◻ |

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS