



PAVE PART #	DESCRIPTION	X	Y
1560	PT12-SS-150-4-TEE12-36-36	36[914.4]MIN	36[914.4]MIN
1560-1	PT12-SS-150-4-TEE12-24-48	24[609.6]MIN	48[1219.2]MIN

**NOTES:**

1. FOR 1560: HE LEAK TEST VACUUM 10X10<sup>-8</sup> CC/SEC OR LESS.
2. FOR 1560-1: LEAK TEST: 500 PSI, NO BUBBLES 1 MINUTE MINIMUM.
3. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
4. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
5. ALL PARTS MUST PASS ALL TESTS.
6. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
7. VOIDS SMALLER THAN  $\phi 0.035$  [.89] ARE ACCEPTABLE.
8. REF-OPERATING TEMPERATURE -20 °C TO 125 °C.
9. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.
10. DIMENSIONS ARE IN INCHES [millimeters].

6	1	EE12 GREEN	WIRE 12EE MIL-W-16878/5 .017 1
5	1	EE12 19STR BLUE	WIRE 12EE MIL-W-16878/5 .017 1
4	1	EE12 19STR RED	WIRE 12EE MIL-W-16878/5 .017 1
3	1	EE12 BLACK	WIRE 12EE MIL-W-16878/5 .017 1
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	3235	HOUSING PT12-SS
ITEM	QTY.	PART NUMBER	DESCRIPTION

**PAVE technology co.**

2751 Thunderhawk Court  
Dayton, OH 45414-3445  
U.S.A.  
tel (937) 890-1100  
fax (937) 8905165  
www.pavetechnologyco.com

DESCRIPTION  
SEE TABLE

PART NUMBER  
**1560**

MATERIAL NOTED

REVISION LEVEL  
A

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.  
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE  $\pm 0.5$   
X.X DECIMAL  $\pm 0.1$  X.XX DECIMAL  $\pm 0.02$  X.XXX DECIMAL  $\pm 0.005$   
ANGLES  $\pm 1$  DEGREE SURFACE FINISH 128 microinch RMS