



NOTES:

1. LEAK TEST:
1589: 80 PSI, NO BUBBLES 7.5 MINUTES MINIMUM.
1589-1: 225 PSI (OPPOSITE DIRECTION).
2. HYPOT 630 VDC 500 MW 0.01 SEC MINIMUM, WIRE TO WIRE.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.

8	4x178	PC28 RED	WIRE 28PVC UL1007 .016 7/#36
7	4x178	PC28 WHITE	WIRE 28PVC UL1007 .016 7/#36
6	4x178	PC28 BROWN	WIRE 28PVC UL1007 .016 7/#36
5	4x178	PC28 BLUE	WIRE 28PVC UL1007 .016 7/#36
4	1	RR 5100-75-HST	RETAINING RING EXTERNAL .750SS
3	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM-BASED
2	1	-016 VITON	O-RING -016 VITON 75
1	A/R	PAVE-Seal 150	EPOXY BLACK
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



DESCRIPTION PAVE-Seal® Cable Harnesses

SPF12-E-80-16-PC28-50-400CM

PART NUMBER

1589

PROJECTION

