



NOTES:

1. HE LEAK TEST @1 ATM. 10^{-8} CC/S.
2. HYPOT 630 VDC 500 MW .01 SEC MINIMUM, WIRE TO WIRE.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL SPECIFICATIONS AND TESTS SUPERSEDE PAVE CATALOG SPECIFICATIONS.

9	31"	E26 RED	WIRE 26E MIL-W-16878/4 7/#34
8	31"	E26 PURPLE	WIRE 26E 7/#34
7	31"	E26 ORANGE	WIRE 26E MIL-W-16878/4 7/#34
6	31"	E26 GREEN	WIRE 26E 7/#34
5	31"	E26 BROWN	WIRE 26E MIL-W-16878/4 7/#34
4	31"	E26 BLUE	WIRE 26E MIL-W-16878/4 7/#34
3	A/R	SUPER O-LUBE	LUBRICANT O-RING SILICONE-BASED
2	1	-010 VITON	O-RING -010 VITON 75
1	1	0168	HOUSING SP6-E

ITEM	QTY	PART#	DESCRIPTION
------	-----	-------	-------------

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION **PAVE-Seal® Cable Harnesses**
SP6-E-200-3TP-TE26-6-24

PART NUMBER **1597**

PROJECTION