



NOTES:

1. HE LEAK TEST @1 ATM. 10^{-8} CC/S.
2. HYPOT 630 VDC 500 MW .01 SEC MINIMUM, WIRE TO WIRE.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL SPECIFICATIONS AND TESTS SUPERSEDE PAVE CATALOG SPECIFICATIONS.

| 5 | 31" | E26 WHITE | WIRE 26E MIL-W-16878/4 7/#34 |
|------|-----|--------------|---------------------------------|
| 4 | 31" | E26 BLACK | WIRE 26E MIL-W-16878/4 7/#34 |
| 3 | A/R | SUPER O-LUBE | LUBRICANT O-RING SILICONE-BASED |
| 2 | 1 | -010 VITON | O-RING -010 VITON 75 |
| 1 | 1 | 0168 | HOUSING SP6-E |
| ITEM | QTY | PART# | DESCRIPTION |

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION **PAVE-Seal® Cable Harnesses**

SP6-E-200-1TP-TE26-6-24

PART NUMBER

1598

PROJECTION

