



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 2 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MW .01 SEC MINIMUM, WIRE TO WIRE.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL SPECIFICATIONS AND TESTS SUPERSEDE PAVE CATALOG SPECIFICATIONS.
5. WIRE POSITIONS ARE APPROXIMATE & COLOR ARRANGEMENT MAY VARY.

7	33"	E24 BLUE	WIRE 24E MIL-W-16878/4 7/#32
6	33"	E24 WHITE	WIRE 24E MIL-W-16878/4 7/#32
5	33"	E24 RED	WIRE 24E MIL-W-16878/4 7/#32
4	33"	E24 BLACK	WIRE 24E MIL-W-16878/4 7/#32
3	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM BASED
2	1	-010 BUNA	O-RING -010 BUNA 70
1	1	0168	HOUSING SP6-E
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION **PAVE-Seal® Cable Harnesses**

SP6-E-150-4-TE24-24-8

PART NUMBER

1599

PROJECTION

