



1623	18.0
1623-1	120.0
PART #	X

NOTES:

1. LEAK TEST: 415 PSI, NO BUBBLES 1 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MΩ 0.01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. PERCENTAGE OF PARTS TESTED WILL BE 100% (MAY BE A LESSER PERCENTAGE FOR LARGE PRODUCTION QUANTITIES, UNLESS OTHERWISE NOTED OR REQUIRED).
5. OPERATING SEAL TEMPERATURE -40° TO 150°C.

3	3	EE12 BLACK	WIRE 12EE MIL-W-16878/5 .017 19/#25
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	0073	HOUSING PTN12-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION PAVE-Seal Cable Harnesses
 PTN12-SS-150-3-TEE12-X-18
 PART NUMBER 1623
 REVISION LEVEL C
 PROJECTION