



- NOTES:**
1. LEAK TEST: 415 PSI, NO BUBBLES 1 MINUTE MINIMUM.
 2. HYPOT 630 VDC 500 MW .01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
 3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
 4. ALL SPECIFICATIONS AND TESTS SUPERSEDE PAVE CATALOG SPECIFICATIONS.

3	A/R	PAVE-Seal 150	EPOXY BLACK
2	3@39	EE8 BLACK	WIRE 8EE MIL-W-16878/5 .020 133/#29
1	1	1132	HOUSING PTN16-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

PAVE Technology

2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION PAVE-Seal@ Cable Harnesses
PTN16-SS-150-3-TEE8-18-18

PART NUMBER 1631	PROJECTION
----------------------------	----------------