



**NOTES:**

1. WIRES MUST BE DIFFERENT COLORS, TO BE DETERMINED BY PAVE STOCK.
2. LEAK TEST: 200 PSI N<sub>2</sub>, 30 SEC MIN., NO BUBBLES.
3. HIPOT TEST: 630VDC, 500MEG OHMS, .01SEC MIN., WIRE TO WIRE TO HOUSING.

4	A/R	PAVE-Seal 80	EPOXY, BLACK
3	13"	PC24	WIRE, 24 AWG, SEE NOTE 1
2	13"	PC24	WIRE, 24 AWG, SEE NOTE 1
1	1	PARKER 2-1 RB-B	HOUSING, PT2-B
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5  
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005  
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



DESCRIPTION  
**PT2-B-80-2-PC24-6-6**

PART NUMBER  
**1676**

