



1693	5 [127]	10 [254]	94-627
1693-1	4 [101.6]	10 [254]	94-589
1693-2	4 [101.6]	25 [635]	TBA
PART#	X	Y	WALBRO#

6	A/R	PAVE-Seal 150	EPOXY BLACK
5	A/R	PARKER-O-LUBE	LUBRICANT O-RING BARIUM-BASED
4	2	-012 VITON	O-RING -012 VITON 75
3	1	PC18 UL1569 RED	WIRE 18PC UL1569 .016 7/#26
2	1	PC18 UL1569 BLK	WIRE 18PC UL1569 .016 7/#26
1	1	1226 SP8L	HOUSING SP8L-E
ITEM	QTY	PART#	DESCRIPTION

- NOTES:
1. LEAK TEST: 80 PSI, NO BUBBLES 1 MINUTE MINIMUM.
  2. NO ELECTRICAL TEST REQUIRED BY WALBRO.
  3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
  4. ALL PARTS MUST PASS ALL TESTS.
  5. WIRES ARE NOT REQUIRED TO BEND SHARPLY AT EPOXY SEAL SURFACE.
  6. NO VOIDS ARE ACCEPTABLE ON O-RING SEALING SURFACES, VOIDS SMALLER THAN ø0.035 [.89] ARE ACCEPTABLE ON ALL OTHER SURFACES.
  7. WIRE POSITIONS ARE APPROXIMATE & VARIABLE.
  8. DIMENSION IS OVER-ALL-LENGTH EXCLUDING OVERFILL ON ATMOSPHERE SIDE OF HOUSING.
  9. (PARTS ARE DEFLASHED ON PARTING LINE +0.005 MAXIMUM.)
  10. DIMENSIONS ARE INCHES [mm].

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5  
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005  
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

**PAVE technology co.**  
 2751 Thunderhawk Court  
 Dayton, Ohio 45414-3445  
 U.S.A.  
 (937)890-1100  
 fax (937)890-5165  
 www.pavetechnologyco.com

DESCRIPTION **PAVE-Seal® Cable Harnesses** SEE CHART  
**SP8L-E-150-2-PC18-4/X-Y**

PART NUMBER **1693**

REVISION LEVEL **D**

PROJECTION