



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 1 MINUTE MINIMUM.
2. HYPOT 630 VDC 500 MΩ .01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE COLOR POSITIONS MAY VARY.
6. DIMENSIONS ARE INCHES [millimeters].
7. NO VOIDS LARGER THAN ∅0.035 [0.89] ARE ACCEPTABLE.
8. REF - OPERATING TEMPERATURE RANGE: 0 TO 80°C.
9. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

5	2	EE18 UL1180 BR	WIRE 18EE UL1180 .014 7/#26
4	2	EE18 UL1180 VI	WIRE 18EE UL1180 19/#
3	2	EE18 UL1180 YEL	WIRE 18EE UL1180 .014 7/#26
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	6-4RB-B	HOUSING PT6-B
ITEM	QTY	PART #	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5  
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005  
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

**PAVE technology co.**  
 2751 Thunderhawk Court  
 Dayton, Ohio 45414-3445  
 U.S.A.  
 (937)890-1100  
 fax (937)890-5165  
 www.pavetechnologyco.com

DESCRIPTION *PAVE-Seal@ Cable Harnesses*  
**PT6-B-80-6-TEE18-6-6**  
 PART NUMBER **1720**  
 REVISION LEVEL **A**  
 PROJECTION