



1756-1	24 [609.6]	24 [609.6]	1 MINUTE MIN
1756	36 [914.4]	240 [6096]	11.5 MINUTES MIN
PART	X	Y	LEAK TEST

NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES, DURATION PER TABLE.
2. HYPOT 630 VDC 500 MΩ 0.01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRES ARE NOT REQUIRED TO BEND SHARPLY AT EPOXY SEAL SURFACE.
6. NO VOIDS LARGER THAN  $\phi 0.035$  [0.89] ARE ACCEPTABLE.
7. REF. - OPERATING TEMPERATURE RANGE: -20 TO 155°C.
8. DIMENSIONS ARE INCHES [mm].

3	A/R	PAVE-Seal 200	EPOXY BLACK
2	2	EE10 BLACK	WIRE 10EE MIL-W-16878/5 .017 37/26
1	1	1132	HOUSING PTN16-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5  
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005  
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

**PAVE technology co.**  
 2751 Thunderhawk Court  
 Dayton, Ohio 45414-3445  
 U.S.A.  
 (937)890-1100  
 fax (937)890-5165  
 www.pavetechnologyco.com

DESCRIPTION PAVE-Seal@ Cable Harnesses  
 PTN16-SS-200-2-TEE10-X-Y

PART NUMBER  
 1756

REVISION LEVEL A  
 PROJECTION