



NOTES:

1. LEAK TEST: 1500 PSI NITROGEN, THREAD SIDE, 10 SECONDS MINIMUM, NO VISIBLE BUBBLES.
2. HYPOT 630 VDC 500 MΩ 0.01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRES ARE NOT REQUIRED TO BEND SHARPLY AT EPOXY SEAL SURFACE.
6. NO VOIDS LARGER THAN 0.035 [.89] ARE ACCEPTABLE.
7. DIMENSIONS ARE INCHES [millimeters].

4	A/R	PAVE-Seal 150	EPOXY BLACK
3	1	3359	HOUSING PT6-SS
2	2	PC22 WHT/RED	WIRE 22PVC UL1569 .016 7/#30
1	2	PC22 WHT/GRN	WIRE 22PVC UL1569 .016 7/#30
ITEM	QTY	ITEM NUMBER	ITEM DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

PAVE technology co.

DESCRIPTION *PAVE-Seal Cable Harnesses*
PT6S-SS-150-4-PC22-14-14

PART NUMBER
1798

REVISION LEVEL
D

PROJECTION