



NOTES:

1. LEAK TEST: 1500 PSI, NO N2 BUBBLES 1 MINUTE MINIMUM.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
6. COSMETIC SURFACE VOIDS LARGER THAN Ø0.035 [0.89] ARE NOT ACCEPTABLE.
7. REF-OPERATING TEMPERATURE -20°C TO 80°C.
8. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.
9. DIMENSIONS ARE INCHES [millimeters].

6	1	IPC28 WHT/BLUE	WIRE 28IPC UL1429 .010 7/#36
5	1	IPC28 ORANGE	WIRE 28IPC UL1429 .010 7/#36
4	1	IPC28 GREY	WIRE 28IPC UL1429 .010 7/#36
3	1	IPC28 BLACK	WIRE 28IPC UL1429 .010 7/#36
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	1592	HOUSING PT4-SS
ITEM	QTY	PART NUMBER	DESCRIPTION

PAVE technology co.

2751 Thunderhawk Court
Dayton, OH 45414-3445
U.S.A.
tel (937) 890-1100
fax (937) 8905165
www.pavetechnologyco.com

DESCRIPTION
PT4-SS-150-4-IPC28-2M-2M

PART NUMBER
1802

MATERIAL NOTED

REVISION LEVEL
A

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5
X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005
ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS