



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 3 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MΩ 0.01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRES ARE NOT REQUIRED TO BEND SHARPLY AT EPOXY SEAL SURFACE.
6. WIRE COLOR POSITIONS MAY VARY.
7. OPERATING TEMPERATURE RANGE -20°C TO 125°C.
8. DIMENSION ARE INCHES [millimeters].

8	1	0183	NUT VS15-SS
7	1	-215 VITON	O-RING -215 VITON 75
6	1	EE12 YELLOW	WIRE 12EE MIL-W-16878/5 .017 19/#25
5	1	EE12 WHITE	WIRE 12EE MIL-W-16878/5 .017 19/#25
4	1	EE12 BLACK	WIRE 12EE MIL-W-16878/5 .017 19/#25
3	1	EE12 GREEN	WIRE 12EE MIL-W-16878/5 .017 19/#25
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	0159	HOUSING VS15-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



DESCRIPTION PAVE-Seal@ Cable Harnesses
VS15-SS-150-4-TEE12-30-40

PART NUMBER	REVISION LEVEL
1806	-
PROJECTION	