



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 1 MINUTE MIN.
2. HYPOT 630 VDC 500 MEGOHMS .01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. WIRE POSITIONS ARE APPROXIMATE ONLY.

| | | | |
|------|------|----------------|-------------------------------------|
| 11 | A/R | PAVE-Seal 150 | EPOXY BLACK |
| 10 | 1@25 | EE22 MIL WHITE | WIRE 22EE MIL-W-16878/5 .014 7/#30 |
| 9 | 1@25 | EE22 MIL ORG | WIRE 22EE MIL-W-16878/5 .014 7/#30 |
| 8 | 1@25 | EE28 19STR GRN | WIRE 28EE MIL-W-16878/5 .014 19/#40 |
| 7 | 1@25 | EE28 19STR BRN | WIRE 28EE MIL-W-16878/5 .014 19/#40 |
| 6 | 1@25 | EE28 19STR BLU | WIRE 28EE MIL-W-16878/5 .014 19/#40 |
| 5 | 1@25 | EE28 19STR BLK | WIRE 28EE MIL-W-16878/5 .014 19/#40 |
| 4 | A/R | PARKER O-LUBE | LUBRICANT O-RING BARIUM |
| 3 | 1 | -112 VITON | O-RING -122 VITON 75 |
| 2 | 1 | 5WLZ-B | NUT VS8-B |
| 1 | 1 | 0393 | HOUSING VS8-B |
| ITEM | QTY | PART# | DESCRIPTION |

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

TITLE OR PAVE ORDER CODE
VS8-B-80-4/2-TEE28/22-12-12

PART NUMBER: **1815** PROJECTION: