


- NOTES:
1. HE LEAK TEST @1 ATM.  $10 \times 10^{-7}$  CC/S OR LESS.
  2. HYPOT 630 VDC 500 MΩ 0.01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
  3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
  4. ALL PARTS MUST PASS ALL TESTS.
  5. WIRES ARE NOT REQUIRED TO BEND SHARPLY AT EPOXY SEAL SURFACE.
  6. WIRE POSITIONS ARE APPROXIMATE AND VARIABLE, COLOR POSITIONS MAY VARY.
  7. NO VOIDS LARGER THAN  $\phi 0.035$  [0.89] ARE ACCEPTABLE.
  8. REF-OPERATING TEMPERATURE RANGE  $-20^{\circ}\text{C}$  TO  $125^{\circ}\text{C}$ .
  9. DIMENSIONS ARE INCHES [millimeters].
  10. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

11	1	0894	NUT VS8-SS
10	1	-112 VITON	O-RING -112 VITON 75
9	1	EE26 UL1180 VIO	WIRE 26EE UL1180 7/#34
8	1	EE26 UL1180 GRN	WIRE 26EE UL1180 7/#34
7	1	EE26 UL1180 RED	WIRE 26EE UL1180 7/#34
6	1	EE26 UL1180 ORG	WIRE 26EE UL1180 7/#34
5	1	EE26 UL1180 GRY	WIRE 26EE UL1180 7/#34
4	1	EE26 UL1180 BLU	WIRE 26EE UL1180 7/#34
3	1	EE26 UL1180 BLK	WIRE 26EE UL1180 7/#34
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	1926	HOUSING VS8-SS REDUCED HEX
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5  
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005  
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS


 2751 Thunderhawk Court  
 Dayton, Ohio 45414-3445  
 U.S.A.  
 (937)890-1100  
 fax (937)890-5165  
 www.pavetechnologyco.com

DESCRIPTION PAVE-Seal® Cable Harnesses  
**VS8-SS-150-7-TEE26-12-12**

PART NUMBER	REVISION LEVEL
1817	B
PROJECTION	