



LEAK TEST PORT
-REF ONLY

- NOTES:
 1. LEAK TEST: 200 PSI, NO BUBBLES 1 MINUTE MINIMUM.
 2. HYPOT 630 VDC 500 MEGOHMS .01 SEC MINIMUM, WIRE TO WIRE.
 3. WIRE POSITIONS ARE APPROXIMATE, & COLOR POSITIONS MAY VARY.

11	1	E14 WHITE	WIRE 14E MIL-W-16878/4 .012 19/#27
10	1	E14 RED	WIRE 14E MIL-W-16878/4 .012 19/#27
9	1	E14 BLACK	WIRE 14E MIL-W-16878/4 .012 19/#27
8	1	E22 23.5" BLUE	WIRE 22E 23.5" MIL-W-16878/4 .010 7/#30
7	1	E22 23.5" BROWN	WIRE 22E 23.5" MIL-W-16878/4 .010 7/#30
6	1	E22 23.5" YELLO	WIRE 22E 23.5" MIL-W-16878/4 .010 7/#30
5	1	E22 23.5" ORANG	WIRE 22E 23.5" MIL-W-16878/4 .010 7/#30
4	1	E22 23.5" GRAY	WIRE 22E 23.5" MIL-W-16878/4 .010 7/#30
3	1	PARKER O-LUBE	LUBRICANT O-RING BARIUM
2	1	-015 VITON	O-RING -015 VITON 75
1	1	1374-M	HOUSING SP11M-E
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

PAVE technology 2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

TITLE OR PAVE ORDER CODE
SP11M-E-150-3/5-TE14/TE22-12-12

PART NUMBER
1845

PROJECTION