


NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 20 SECONDS MINIMUM.
2. HYPOT 630 VDC 500 MEGOHMS .01 SEC MINIMUM, WIRE TO WIRE.
3. WIRE POSITIONS ARE APPROXIMATE, & COLOR POSITIONS MAY VARY.


5	A/R	PAVE-Seal 150	EPOXY BLACK
4	9.2"	EE12 FEP RED	WIRE 12FEP TYPE K
3	9.2"	EE12 FEP WHT	WIRE 12FEP TYPE K
2	9.2"	EE12 FEP BLUE	WIRE 12FEP TYPE K
1	1	12-8RB-S	HOUSING PT12-PS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION
PT12-PS-150-3-TEE12-4-4

PART NUMBER 1860	PROJECTION 
----------------------------	----------------------------------------------------------------------------------------------------