



NOTES:

1. LEAK TEST: NITROGEN OR AIR @ 1000 PSI FOR 5 MINUTES MINIMUM AT ROOM TEMPERATURE.
2. HYPOT 630 VDC 500 MEGOHMS .01 SEC MINIMUM, WIRE TO WIRE & HOUSING AT ROOM TEMPERATURE.
3. THERMAL CYCLE PRIOR TO ALL TESTING: -40°C TO 80°C 1 HOUR SOAK FOR 3 CYCLES MINIMUM.
4. POTTED WIRE POSITIONS & COLOR MAY VARY.

11	1	EE22 WHT	WIRE 22E MIL-W-16878/4 .010 7/#30
10	1	EE22 GRAY	WIRE 22E MIL-W-16878/4 .010 7/#30
9	1	EE22 VIOLET	WIRE 22E MIL-W-16878/4 .010 7/#30
8	1	EE22 BLUE	WIRE 22E MIL-W-16878/4 .010 7/#30
7	1	EE22 GREEN	WIRE 22E MIL-W-16878/4 .010 7/#30
6	1	EE22 YELLOW	WIRE 22E MIL-W-16878/4 .010 7/#30
5	1	EE22 ORANGE	WIRE 22E MIL-W-16878/4 .010 7/#30
4	1	EE22 RED	WIRE 22E MIL-W-16878/4 .010 7/#30
3	1	EE22 BROWN	WIRE 22E MIL-W-16878/4 .010 7/#30
2	1	PAVE SEAL 150	EPOXY BLACK
1	1	0346	HOUSING PT8-SS
ITEM	QTY	PART#	DESCRIPTION

PAVE technology co.

2751 Thunderhawk Court
Dayton, Ohio 45414-3445
U.S.A.
(937)890-1100
fax (937)890-5165
www.pavetechnologyco.com

TITLE OR PAVE ORDER CODE
PT8-SS-150-9-TE22-12-12

PART NUMBER
1892

PROJECTION