



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 1 MINUTE MINIMUM.
2. HYPOT 630 VDC 500 M .01 SBC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL SPECIFICATIONS AND TESTS SUPERSEDE PAVE CATALOG SPECIFICATIONS.
5. WIRE POSITIONS APPROXIMATE AND COLOR ARRANGEMENTS ARE RANDOM.

14	22.7"	PC22 UL1569 YEL	WIRE 22PVC UL1569 .016 7/#30
13	22.7"	PC22 UL1569 RED	WIRE 22PVC UL1569 .016 7/#30
12	22.7"	PC22 UL1569 PUR	WIRE 22PVC UL1569 .016 7/#30
11	22.7"	PC22 UL1569 ORG	WIRE 22PVC UL1569 .016 7/#30
10	22.7"	PC22 UL1569 GRY	WIRE 22PVC UL1569 .016 7/#30
9	22.7"	PC22 UL1569 GRN	WIRE 22PVC UL1569 .016 7/#30
8	22.7"	PC22 UL1569 BRN	WIRE 22PVC UL1569 .016 7/#30
7	22.7"	PC22 UL1569 BLU	WIRE 22PVC UL1569 .016 7/#30
6	22.7"	PC14 UL1015 RED	WIRE 14PVC UL1015 .031 41/#30
5	22.7"	PC14 UL1015 BLK	WIRE 14PVC UL1015 .031 41/#30
4	A/R	EN-1556 BLACK	URETHANE BLACK
3	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM
2	1	-016 VITON	O-RING -016 VITON 75
1	1	0130	HOUSING SPF12-E
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



DESCRIPTION
 SPF12-E-150-2/8-PC14/22-8-14

PART NUMBER

1895

PROJECTION

