



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 13 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 M .01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL SPECIFICATIONS AND TESTS SUPERSEDE PAVE CATALOG SPECIFICATIONS.

3	A/R	PAVE-Seal 150	EPOXY BLACK
2	314"	AWC1165-13J	CABLE UL 20230 13-20ET
1	1	1625	HOUSING PT16-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

2751 Thunderhawk Court
Dayton, Ohio 45414-3445
U.S.A.
(937)890-1100
fax (937)890-5165
www.pavetechnologyco.com

DESCRIPTION PAVE-Seal® Cable Harnesses
PT16-SS-150-1-AWC1165-13J-240-72

PART NUMBER
1935

PROJECTION