



**NOTES:**

1. HE LEAK TEST @1 ATM. <math>10^{-8}</math> CC/S (VACUUM ON THREAD SIDE FOR TESTING).
2. HYPOT 630 VDC 500 M .01 SBC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL SPECIFICATIONS AND TESTS SUPERSEDE PAVE CATALOG SPECIFICATIONS.
5. WIRE POSITIONS & COLOR ARRANGMENTS ARE APPROXIMATE.

10	1@50	EE16 BLACK	WIRE 16EE MIL-W-16878/5 .015 19/#29
9	1@50	EE16 GREEN	WIRE 16EE MIL-W-16878/5 .015 19/#29
8	1@50	EE16 VIOLET	WIRE 16EE MIL-W-16878/5 .015 19/#29
7	1@50	EE16 WHITE	WIRE 16EE MIL-W-16878/5 .015 19/#29
6	2@50	KT24	CABLE T/C TYPE K 24AWG TEFLON
5	A/R	PAVE-Seal 150	EPOXY BLACK
4	A/R	SUPER O-LUBE	LUBRICANT O-RING SILICONE
3	1	-116 VITON	O-RING -116 VITON 75
2	1	8L5N-SS	NUT VS12-SS
1	1	1180	HOUSING VS12L-SS
ITEM	QTY	PART #	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5  
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005  
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



DESCRIPTION PAVE-Seal® Cable Harnesses  
 VS12L-SS-150-4/2P-TEE16/KT24-24-24

PART NUMBER  
**1952**

