



NOTES:

1. LEAK TEST: 1200 PSI, NO BUBBLES 30 SECONDS MINIMUM.
2. HYPOT 630 VDC 500 MW .01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL SPECIFICATIONS AND TESTS SUPERSEDE PAVE CATALOG SPECIFICATIONS.

8	A/R	PAVE-Seal 150	EPOXY BLACK
7	4"	FIT 105-1/4	TUBING SHRINK 1/4" IRR. PVC MIL-I-23053/2C BLK
6	9.2"	PC22 UL1569 BLU	WIRE 22PVC UL1569 .016 7/#30
5	9.2"	PC22 UL1569 WHT	WIRE 22PVC UL1569 .016 7/#30
4	9.2"	PC22 UL1569 YEL	WIRE 22PVC UL1569 .016 7/#30
3	9.2"	PC22 UL1569 BLK	WIRE 22PVC UL1569 .016 7/#30
2	9.2"	PC22 UL1569 RED	WIRE 22PVC UL1569 .016 7/#30
1	1	1971	HOUSING PT12-B
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG. SURFACE FINISH 128 microinch RMS

2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION PAVE-Seal® Cable Harnesses
PT12-B-150-5-PC22-4-4

PART NUMBER 1970	PROJECTION
----------------------------	----------------