



**NOTES:**

1. LEAK TEST: 400 PSI, NO BUBBLES 1 MINUTE MINIMUM W/ 1372.
2. HYPOT 630 VDC 500 MW .01 SEC MINIMUM, WIRE TO WIRE.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL SPECIFICATIONS AND TESTS SUPERSEDE PAVE CATALOG SPECIFICATIONS.
5. WIRE COLOR ARRANGEMENT & WIRE SPACING VARIES.

10	1@25	PC22 UL1061 VIO	WIRE 22PVC UL1061 .010 7#30
9	1@25	PC22 UL1061 ORA	WIRE 22PVC UL1061 .010 7#30
8	2@25	PC22 UL1061 YEL	WIRE 22PVC UL1061 .010 7#30
7	1@25	PC22 UL1061 GRN	WIRE 22PVC UL1061 .010 7#30
6	1@25	PC22 UL1061 RED	WIRE 22PVC UL1061 .010 7#30
5	1@25	PC22 UL1061 BLU	WIRE 22PVC UL1061 .010 7#30
4	2@25	PC22 UL1061 BLK	WIRE 22PVC UL1061 .010 7#30
3	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM
2	2	-012 BUNA	O-RING -012 BUNA 75
1	1	1226 SP8M	HOUSING SP8M-E
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5  
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005  
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



DESCRIPTION PAVE-Seal® Cable Harnesses  
 SP8M-E-150-9-PC22-12-12

PART NUMBER  
 2018

