



**NOTES:**

1. LEAK TEST: 80 PSI, NO BUBBLES 30 SECONDS MINIMUM.
2. HYPOT 630 VDC 500 MEGOHMS .01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE DONE AT ROOM TEMPERATURE.
4. THESE SPECIFICATIONS SUPERSEDE PAVE CATALOG.

4	A/R	PAVE-Seal 80	EPOXY BLACK
3	10"	PC22 UL1569 RED	WIRE 22PVC UL1569 .016 7/#30
2	10"	PC22 UL1569 BLK	WIRE 22PVC UL1569 .016 7/#30
1	1	0120-SS	HOUSING PT2-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-5  
 X DECIMAL +/- .1 XX DECIMAL +/- .02 XXX DECIMAL +/- .005  
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

**PAVE Technology Co.**

2751 Thunderhawk Court  
 Dayton, Ohio 45414-3445  
 U.S.A.  
 (937)890-1100  
 fax (937)890-5165  
 www.pavetechnologyco.com

DESCRIPTION PAVE-Seal® Cable Harnesses  
**PT2-SS-80-2-PC22-4.5-4.5**

PART NUMBER  
**2021**

PROJECTION