



NOTES:

1. LEAK TEST: 2000 PSI, NO BUBBLES 2 MINUTES MIN.
2. HYPOT 630 VDC 500 MEGOHMS .01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE DONE AT ROOM TEMPERATURE.
4. THESE SPECIFICATIONS SUPERSEDE PAVE CATALOG.
5. REF-PARTS TO SEE 350°C DURING USE ON PRESSURE SIDE.
6. MAY BE USED FOR EVALUATION ON A SET NUMBER OF ASSEMBLIES.

6	1x18"	E24 RED	WIRE 24E UL1213 7/#32 RED
5	1x18"	E24 BLACK	WIRE 24E UL1213 7/#32 BLACK
4	A/R	PAVESeal 1260	CERAMIC HI-TEMP (OPTIONAL-SEE NOTE 6)
3	1	-903 VITON	O-RING -903 VITON 75 DURO
2	A/R	PAVESeal 150FR	EPOXY FLAME RETARDANT BLACK
1	1	2043	HOUSING SO6-SS
ITEM	QTY	PART NUMBER	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

PAVE technology co. 2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION
SO6-SS-150FR-1TP-TE24-12-4

PART NUMBER
2031

PROJECTION