



NOTES:

1. LEAK TEST: 400 PSI N2 NO BUBBLES 1.5 MINUTES MINIMUM.
QUALIFICATION ONLY: <10-6 STD CC/SEC HELIUM LEAK TEST.
2. HYPOT 630 VDC 500 MEGOHMS .01 SEC MINIMUM, WIRE TO WIRE.
3. ALL ELECTRICAL & LEAK TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. THIS DRAWING SUPERSEDES PAVE CATALOG SPECIFICATIONS.

7	31"	E24 YLW	WIRE 24E MIL-W-22459/11 .010 19/#36
6	31"	E24 WHT	WIRE 24E MIL-W-22459/11 .010 19/#36
5	31"	E24 RED ML	WIRE 24E MIL-W-22459/11 .010 19/#36
4	31"	E24 BLK	WIRE 24E MIL-W-22459/11 .010 19/#36
3	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM
2	1	-010 FLURO	O-RING -010 SILICONE 70 M25988/1
1	1	0168	HOUSING SP6-E

ITEM	QTY	PART#	DESCRIPTION
ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS			

PAVE technology 

2751 Thunderhawk Court
Dayton, Ohio 45414-3445
U.S.A.
(937)890-1100
fax (937)890-5165
www.pavetechnologyco.com

DESCRIPTION **PAVE-Seal® Cable Harnesses**
SP6-E-200-4-TE24-6-24

PART NUMBER **2041**

PROJECTION 