



BULKHEAD
32 RMS OR BETTER
FINISH REQUIRED ON
A SPOT FACE FOR
O-RING SEAL

2111-6	EE12 VIOLET
2111-5	EE12 BLACK
2111-4	EE12 WHITE
2111-3	EE12 GREEN
2111-2	EE12 RED
2111-1	EE12 BLUE
PAVE#	WIRE PART#

NOTES:

1. HE LEAK TEST @1 ATM. 10^{-7} CC/S.
2. HYPOT 630 VDC 500 MW .01 SEC MINIMUM, WIRE TO HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL SPECIFICATIONS AND TESTS SUPERSEDE PAVE CATALOG SPECIFICATIONS.

6	1	0894	NUT VS8-SS SPIRALOCK
5	A/R	SUPER O-LUBE	LUBRICANT O-RING SILICONE
4	1	-112 VITON	O-RING -112 VITON 75A
3	97"	[SEE TABLE]	WIRE 12EE MIL-W-16878/5 .017 19/#25
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	0892	HOUSING VS8-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
.X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
ANGLES +/- 1 DEG. SURFACE FINISH 128 microinch RMS



DESCRIPTION PAVE-Seal® Cable Harnesses
VS8-SS-150-1-TEE12-72-24

PART NUMBER

2111

PROJECTION

