



NOTES:

1. HE LEAK TEST @1 ATM. 10^{-8} CC/S.
2. HYPOT 630 VDC 500 MW .01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL SPECIFICATIONS AND TESTS SUPERSEDE PAVE CATALOG SPECIFICATIONS.
5. WIRE POSITIONS & COLOR ARRANGMENTS ARE APPROXIMATE.

8	25"	E22 BLK	WIRE 22E MIL-W-16878/4 .010 7/#30
7	25"	E22 WHT	WIRE 22E MIL-W-16878/4 .010 7/#30
6	25"	E22 GRAY	WIRE 22E MIL-W-16878/4 .010 7/#30
5	A/R	SUPER O-LUBE	LUBRICANT O-RING SILICONE
4	1	-112 VITON	O-RING -112 VITON 75A
3	1	0894	NUT VS8-SS SPIRALOCK
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	0892	HOUSING VS8-SS

ITEM	QTY	PART#	DESCRIPTION
ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES			
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5			
.X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005			
ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS			

BULKHEAD-REF ONLY
 32 RMS OR BETTER
 FINISH REQUIRED ON
 .88 MIN SPOT FACE
 FOR O-RING SEAL



DESCRIPTION PAVE-Seal® Cable Harnesses
VS8-SS-80-3-TE22-12-12

PART NUMBER

2113

PROJECTION

