



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 30 SECONDS MINIMUM.
2. HYPOT 630 VDC 500 MEGOHMS 0.01 SEC MINIMUM, WIRE TO WIRE.
3. ALL TESTS ARE DONE AT ROOM TEMPERATURE.
4. WIRES MUST BEND 90° WITHIN 0.25" OF EXITING THE EPOXY.

11	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM-BASED
10	1	-016 VITON	O-RING -016 VITON 75
9	21"	E26 YELLOW	WIRE 26E MIL-W-16878/4 7/#34
8	21"	E26 ORANGE	WIRE 26E MIL-W-16878/4 7/#34
7	21"	E26 GREEN	WIRE 26E MIL-W-16878/4 7/#34
6	21"	E26 BROWN	WIRE 26E MIL-W-16878/4 7/#34
5	21"	E26 BLUE	WIRE 26E MIL-W-16878/4 7/#34
4	21"	E14 WHITE	WIRE 14E MIL-W-16878/4 .012 19/#27
3	21"	E14 RED	WIRE 14E MIL-W-16878/4 .012 19/#27
2	21"	E14 BLACK	WIRE 14E MIL-W-16878/4 .012 19/#27
1	A/R	PAVE-Seal 150	EPOXY BLACK
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS


 2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION **PAVE-Seal® Cable Harnesses**
SP12X-E-150-3/5-TE14/26-12-4
 PART NUMBER **2153**
 PROJECTION 