



USE TRUARC N5000-50 RETAINING RING OR EQUAL.
IF REMOVED FROM PORT, REPLACE O-RINGS.

- NOTES:
1. LEAK TEST: 80 PSI, NO BUBBLES 40 SECONDS MINIMUM. A GREEN PAINT DOT INDICATES THE PART HAS PASSED THE TEST.
 2. HIPOT 630 VDC 500 MΩ .01 SEC MINIMUM, WIRE TO WIRE.
 3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
 4. ALL PARTS MUST PASS ALL TESTS.
 5. DIMENSIONS ARE INCHES [millimeters].
 6. NO VOIDS LARGER THAN $\phi 0.035$ [0.89] ARE ACCEPTABLE.
 7. REF - OPERATING TEMPERATURE RANGE: -20 TO 125°C.
 8. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

7	2	-012 VITON	O-RING -012 VITON 75
6	A/R	PARKER-O-LUBE	LUBRICANT O-RING BARIUM BASED
5	1	PC18 UL1569 WHT	WIRE 18PC UL1569 .016 7/#26
4	1	PC18 UL1569 RED	WIRE 18PC UL1569 .016 7/#26
3	1	PC18 UL1569 BLK	WIRE 18PC UL1569 .016 7/#26
2	1	PC18 UL1569 GRN	WIRE 18PC UL1569 .016 7/#26
1	1	1226L	HOUSING SP8L-E
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION
SP8L-E-150-4-PC18-8-8

PART NUMBER
2169

REVISION LEVEL
B

PROJECTION