


- NOTES:**
1. LEAK TEST IN NOTED DIRECTION (UNIT CAN WITHSTAND PRESSURE BIDIRECTIONALLY): 450 PSI, NO BUBBLES 30 SECONDS MINIMUM.
 2. HYPOT 630 VDC 500 MW 0.01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
 3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.

3	2@20'	8K	WIRE 8 KANTHAL BARE
2	A/R	PAVE-Seal 200	EPOXY BLACK
1	1	0073	HOUSING PTN12-SS
ITEM	QTY	PART NUMBER	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS


 2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION PAVE-Seal® Cable Harnesses
PTN12-SS-200-2-8K-24-216

PART NUMBER
2243

PROJECTION
