



NOTES:

1. LEAK TEST: 80 PSI N2, NO BUBBLES 0.5 MINUTE MINIMUM.
2. HYPOT 630 VDC 500 MΩ 0.01 SEC MINIMUM, WIRE TO WIRE.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRES ARE NOT REQUIRED TO BEND SHARPLY AT EPOXY SEAL SURFACE.
6. NO VOIDS LARGER THAN ø.035 [.89] ARE ACCEPTABLE.
7. FLASH REMOVED ON "GASKET SIDE" SURFACE OF ITEM 1.
8. WIRE COLOR POSITIONS ARE VARIABLE.
9. REF-OPERATING TEMPERATURE RANGE -55°C TO 125°C.
10. DIMENSIONS ARE INCHES [millimeters].

17	1	E26 WHT/GRY 1 S	WIRE 26E MIL-W-16878 SOLID CONDUCTOR
16	1	E26 WHT/BRN 1 S	WIRE 26E MIL-W-16878 SOLID CONDUCTOR
15	1	E26 WHT/ORG 1 S	WIRE 26E MIL-W-16878 SOLID CONDUCTOR
14	1	E26 WHT/GRN 1 S	WIRE 26E MIL-W-16878 SOLID CONDUCTOR
13	1	E26 WHT/BLU 1 S	WIRE 26E MIL-W-16878 SOLID CONDUCTOR
12	1	E26 WHT/VIO 1 S	WIRE 26E MIL-W-16878 SOLID CONDUCTOR
11	1	E26 WHT/RED 1 S	WIRE 26E MIL-W-16878 SOLID CONDUCTOR
10	1	E26 RED 1 STRD	WIRE 26E MIL-W-16878 SOLID CONDUCTOR
9	1	E26 VIO 1 STRD	WIRE 26E MIL-W-16878 SOLID CONDUCTOR
8	1	E26 BLUE 1 STRD	WIRE 26E MIL-W-16878 SOLID CONDUCTOR
7	1	E26 GRE 1 STRD	WIRE 26E MIL-W-16878 SOLID CONDUCTOR
6	1	E26 YLW 1 STRD	WIRE 26E MIL-W-16878 SOLID CONDUCTOR
5	1	E26 ORG 1 STRD	WIRE 26E MIL-W-16878 SOLID CONDUCTOR
4	1	E26 BRN 1 STRD	WIRE 26E MIL-W-16878 SOLID CONDUCTOR
3	1	E26 GREY 1 STRD	WIRE 26E MIL-W-16878 SOLID CONDUCTOR
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	CONXALL P5633	HOUSING NYLON + GASKET + HEX NUT
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

PAVE technology co.

DESCRIPTION PAVE-Seal Cable Harnesses
CON610-N-15-TE26-6-6

PART NUMBER
2244

REVISION LEVEL
D

PROJECTION