



**NOTES:**

1. LEAK TEST: 375 PSI, NO BUBBLES 1 MINUTE MINIMUM.
2. HYPOT 630 VDC 500 MW 0.01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.

6	4FT	E12 RED	WIRE 14E MIL-W-16878/4 .012 19/#27
5	4FT	E12 WHITE	WIRE 12E MIL-W-16878/4 .013 19/#25
4	A/R	PAVE-Seal 80	EPOXY BLACK
3	1	-908 BUNA	O-RING -908 BUNA 90
2	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM-BASED
1	1	8P50N-SS	HOUSING SO12-SS
<b>ITEM</b>	<b>QTY</b>	<b>PART#</b>	<b>DESCRIPTION</b>

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN MM  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-13  
 .X DECIMAL +/- 2.5 .XX DECIMAL +/- .50 .XXX DECIMAL +/- .100  
 ANGLES +/- 1 DEG SURFACE FINISH 3.2 micrometers RMS

2751 Thunderhawk Court  
Dayton, Ohio 45414-3445  
U.S.A.  
(937)890-1100  
fax (937)890-5165  
www.pavetechnologyco.com

DESCRIPTION **PAVE-Seal® Cable Harnesses**  
**SO12-SS-80-2-TE12-60-60cm**

PART NUMBER <b>2297</b>	PROJECTION 
----------------------------	----------------