



NOTES:

1. HE LEAK TEST @1 ATM. 10^{-7} CC/S.
2. RESISTANCE CHECK -
 - a. WIRE END TO END 800-1200 W @25°C (THERMISTOR @25°C IS 1000 W \pm 20%.)
 - b. WIRE LEADS TO HOUSING >20 MW
3. PROTECT ITEM 4 PRIOR TO SHIPPING.
4. STORAGE TEMPERATURE -40°C TO 65°C
5. ITEM 4 IS CUSTOMER SUPPLIED.
6. DESIGN QUALIFICATION TEST TO 600 PSI NITROGEN THREAD SIDE NO VISIBLE BUBBLES.
7. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.

5	A/R	SOLDER .025	SOLDER SN60 #66 CORE FLUX 44
4	1	FENWAL# 112-102EAJ-B01	THERMISTOR GLASS BEAD .04"
3	2@3	ET28 WHITE	WIRE 28ET MIL-W-16878/6 .006 7/#36
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	2326	HOUSING PT4-B (SMALL)
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



DESCRIPTION PAVE-Seal® Cable Harnesses
 PT4-B-150-2-TET28-.29GT-2.25

PART NUMBER
 2324

