


18	EE22 MIL BRN
17	EE22 MIL VIO
16	EE20 MIL BLK
15	EE22 W/RED+GREY
14	EE22 MIL ORG
13	EE22 MIL BLUE
12	EE22 MIL RED
11	EE22 MIL W/BLK
10	NOT USED
9	EE22 MIL GRAY
8	NOT USED
7	EE22 MIL GREEN
6	EE22 MIL W/GRN
5	NOT USED
4	NOT USED
3	EE22 MIL YLW
2	EE22 MIL W/RED
1	EE22 MIL WHITE
SOC#	PART#



VIEW A-A

18	1	13280-18SG-326	CONNECTOR MAXI-CON-X CABLE 18-#20 SOCS
17	A/R	EN-1556 BLACK	URETHANE MIL-M-24021C NON-MBOC
16	146"	EE22 MIL W/RED	WIRE 22EE MIL-W-16878/5 .015 7/#30
15	146"	EE22 MIL W/GRN	WIRE 22EE MIL-W-16878/5 .015 7/#30
14	146"	EE22 MIL W/BLK	WIRE 22EE MIL-W-16878/5 .015 7/#30
13	146"	EE22 W/RED+GREY	WIRE 22EE MIL-W-16878/5 .015 7/#30
12	146"	EE22 MIL YLW	WIRE 22EE MIL-W-16878/5 .015 7/#30
11	146"	EE22 MIL WHITE	WIRE 22EE MIL-W-16878/5 .015 7/#30
10	146"	EE22 MIL VIO	WIRE 22EE MIL-W-16878/5 .015 7/#30
9	146"	EE22 MIL RED	WIRE 22EE MIL-W-16878/5 .015 7/#30
8	146"	EE22 MIL ORG	WIRE 22EE MIL-W-16878/5 .015 7/#30
7	146"	EE22 MIL GREEN	WIRE 22EE MIL-W-16878/5 .015 7/#30
6	146"	EE22 MIL GRAY	WIRE 22EE MIL-W-16878/5 .015 7/#30
5	146"	EE22 MIL BRN	WIRE 22EE MIL-W-16878/5 .015 7/#30
4	146"	EE22 MIL BLUE	WIRE 22EE MIL-W-16878/5 .015 7/#30
3	146"	EE22 MIL BLK	WIRE 22EE MIL-W-16878/5 .015 7/#30
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	1625	HOUSING PT16-SS
ITEM	QTY	PART#	DESCRIPTION

- NOTES:
1. LEAK TEST: 80 PSI, NO BUBBLES 6 MINUTES MINIMUM.
  2. HYPOT 630 VDC 500 MW 0.01 SEC MINIMUM, WIRE TO WIRE & HOUSING
  3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
  4. CONTINUITY TEST WIRE END TO SOCKET <0.22W.

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5  
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005  
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

2751 Thunderhawk Court  
 Dayton, Ohio 45414-3445  
 U.S.A.  
 (937)890-1100  
 fax (937)890-5165  
 www.pavetechnologyco.com

DESCRIPTION PAVE-Seal® Cable Harnesses  
**PT16-SS-150-14-TEE22-72-72**

PART NUMBER  
**2328**

PROJECTION