



NOTES:

1. HE LEAK TEST @1 ATM. 10×10^{-7} CC/S OR LESS.
2. HYPOT 630 VDC 500 M Ω .01 SEC MINIMUM, WIRE TO WIRE, SHIELD & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. FINISH APPLIES TO SPOTFACE FOR O-RING SEAL ONLY.
6. DIMENSIONS ARE INCHES [millimeters].
7. NO VOIDS LARGER THAN $\phi 0.035$ [0.89] ARE ACCEPTABLE.
8. REF - OPERATING TEMPERATURE RANGE: -20 TO 125°C.
9. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

5	1	-215 VITON	O-RING -215 VITON 75
4	1	0183	NUT VS15-SS
3	A/R	PAVE-Seal 150	EPOXY BLACK
2	2	M27500-12RE2N06	CABLE 2/C #12 TSJ
1	1	0161	HOUSING VS15L-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

PAVE technology co.

DESCRIPTION PAVE-Seal@ Cable Harnesses
 VS15L-SS-150-2TSJP-12RE2N06-48-48

PART NUMBER
2349

REVISION LEVEL
A

PROJECTION