



- NOTES:
1. HE LEAK TEST @1 ATM. 10^{-8} CC/S.
 2. HYPOT 630 VDC 500 MW 0.01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
 3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
 4. WIRE COLOR ARRANGEMENTS MAY VARY.

10	1	-215 VITON	O-RING -215 VITON 75
9	A/R	PAVE-Seal 200FR	EPOXY BLACK
8	A/R	SUPER O-LUBE	LUBRICANT O-RING SILICONE BASED
7	1	0183	NUT VS15-SS
6	50"	EE12 19STR RED	WIRE 12EE MIL-W-16878/5 .017 19/#25
5	50"	EE12 19STR BLUE	WIRE 12EE MIL-W-16878/5 .017 19/#25
4	50"	EE12 GREEN	WIRE 12EE MIL-W-16878/5 .017 19/#25
3	50"	EE12 WHITE	WIRE 12EE MIL-W-16878/5 .017 19/#25
2	50"	EE12 BLACK	WIRE 12EE MIL-W-16878/5 .017 19/#25
1	1	0161	HOUSING VS15L-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

PAVE Technology Co.

DESCRIPTION *PAVE-Seal@ Cable Harnesses*
VS15L-SS-200FR-5-TEE12-24-24

PART NUMBER
2385

PROJECTION