


| | |
|-------------|--------------|
| 2408-3 | PC2 GRN |
| 2408-2 | PC2 BLUE |
| 2408-1 | PC2 BLK |
| 2408 | PC2 RED |
| PART NUMBER | ITEM 3 PART# |

NOTES:


1. LEAK TEST: 170 PSI, NO BUBBLES 7.5 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MΩ 0.01 SEC MINIMUM, WIRE TO HOUSING.
3. CONTINUITY TEST WIRE END TO END: <6mΩ.
4. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.

| 3 | 1 | SEE TABLE | WIRE 2PC UL1283 19/.0591 .419 |
|------|-----|---------------|-------------------------------|
| 2 | A/R | PAVE-Seal 150 | EPOXY BLACK |
| 1 | 1 | 8-4RB-SS | HOUSING PT8-SS |
| ITEM | QTY | PART# | DESCRIPTION |


 2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION **PAVE-Seal Cable Harnesses**
PT8-SS-150-1-PC2-120-240

PART NUMBER
2408

REVISION LEVEL **A**
 PROJECTION 

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS