



NOTES:

1. ALL PARTS ARE CAPABLE OF PASSING: 5 BAR (75 PSI-REF) MINIMUM LEAK TEST, NO AIR BUBBLES, 4 MINUTES MINIMUM.
2. ALL PARTS ARE CAPABLE OF PASSING A HYPOT TEST- 630 VDC 500 MW 0.01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. WIRE POSITIONING IS APPROXIMATE & VARIABLE.

7	1@8'	E26 GREEN	WIRE 26E MIL-W-16878/4 7#34
6	1@8'	E26 BROWN 7 STR	WIRE 26E MIL-W-16878/4 7#34
5	1@8'	E14 BLUE	WIRE 14E MIL-W-16878/4 .012 19/#27
4	1@8'	E14 ORANGE	WIRE 14E MIL-W-16878/4 .012 19/#27
3	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM-BASED
2	2	-015 VITON	O-RING -015 VITON 75
1	1	1374 SP11M	HOUSING SP11M-E
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN MM
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-13
 .X DECIMAL +/- 2.5 .XX DECIMAL +/- .50 .XXX DECIMAL +/- .100
 ANGLES +/- 1 DEG SURFACE FINISH 3.2 micrometers RMS

2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

PAVE Technology Co.

DESCRIPTION **PAVE-Seal® Cable Harnesses**
SP11M-E-150-2/2-E14/26-160-80cm

PART NUMBER **2412**

PROJECTION