



NOTES:

1. LEAK TEST: 380 PSI, NO BUBBLES 1 MINUTE MINIMUM. (UNIT CAN WITHSTAND PRESSURE BIDIRECTIONALLY)
2. HYPOT 800 VDC 10 MΩ 0.01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRES ARE NOT REQUIRED TO BEND SHARPLY AT EPOXY SEAL SURFACE.
6. NO VOIDS LARGER THAN $\phi 0.035$ [0.89] ARE ACCEPTABLE.
7. WIRE COLOR POSITIONS MAY VARY.
8. DIMENSIONS ARE INCHES [millimeters].

14	1	EE22 UL WHT/BLU	WIRE 22EE UL1180 STRIPE 7/30
13	1	EE22 UL WHT/RED	WIRE 22EE UL1180 STRIPE 7/30
12	1	EE22 UL1180 BLK	WIRE 22EE UL1180 MARKED 7/#30
11	1	EE22 UL1180 BLU	WIRE 22EE UL1180 7/#30 BLUE
10	1	EE22 UL1180 BRN	WIRE 22EE UL1180 MARKED 7/#30
9	1	EE22 UL1180 GRN	WIRE 22EE UL1180 MARKED 7/#30
8	1	EE22 UL1180 GRY	WIRE 22EE UL1180 7/30
7	1	EE22 UL1180 ORG	WIRE 22EE UL1180 7/#30 ORANGE
6	1	EE22 UL1180 RED	WIRE 22EE UL1180 MARKED 7/#30
5	1	EE22 UL1180 VIO	WIRE 22EE UL1180 7/#30
4	1	EE22 UL1180 WHT	WIRE 22EE UL1180 MARKED 7/#30
3	1	EE22 UL1180 YLW	WIRE 22EE UL1180 7/#30 YELLOW
2	A/R	PAVE-Seal 200	EPOXY BLACK
1	1	0073	HOUSING PTN12-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION PAVE-Seal@ Cable Harnesses
PTN12-SS-200-12-TEE22-17-17
 PART NUMBER **2466**
 REVISION LEVEL **B**
 PROJECTION