



NOTES:

1. HE LEAK TEST @1 ATM. 10^{-7} CC/S.
2. HYPOT 630 VDC 500 MW 0.01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. PERCENTAGE OF PARTS TESTED WILL BE 100% (MAY BE

A LESSER PERCENTAGE FOR LARGE PRODUCTION QUANTITIES, UNLESS OTHERWISE NOTED OR REQUIRED).

6	A/R	EE12 WHITE	WIRE 12EE MIL-W-16878/5 .017 19/25
5	A/R	EE12 GREEN	WIRE 12EE MIL-W-16878/5 .017 19/25
4	A/R	EE12 19STR RED	WIRE 12EE MIL-W-16878/5 .017 19/25
3	1	EE12 19STR BLUE	WIRE 12EE MIL-W-16878/5 .017 19/25
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	12-8RB-B	PT12-B HOUSING
ITEM	QTY	ITEM NUMBER	ITEM DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION **PAVE-Seal® Cable Harnesses**

PT12-B-150-4-TEE12-36-36

PART NUMBER	REVISION LEVEL
2484	-
PROJECTION	