



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 1.5 MINUTES MINIMUM.
2. HYPOT 1000 VDC 500 MEGAOHMS MINIMUM 0.01 MINUTE MINIMUM WIRE TO WIRE.
3. WIRE COLOR POSITIONS MAY VARY.
4. WIRES MAY NOT BE FULLY FLEXIBLE WHERE THEY EXIT THE HOUSING.
5. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
6. PERCENTAGE OF PARTS TESTED WILL BE 100% (MAY BE A LESSER PERCENTAGE FOR LARGE PRODUCTION QUANTITIES, UNLESS OTHERWISE NOTED OR REQUIRED).

12	2	FIT-350-3/16	TUBING SHRINK 3/16" KYNAR CLEAR
11	4	FIT-350-3/8	TUBING SHRINK 3/8" KYNAR CLEAR
10	1	XLP8 BLK W/GRN	WIRE 8XLP UL3321 C-L POLYOLEFIN
9	1	XLP8 BLK W/RED	WIRE 8XLP UL3321 C-L POLYOLEFIN
8	1	XLP8 BLK W/WHT	WIRE 8XLP UL3321 C-L POLYOLEFIN
7	1	XLP8 BLK W/PUR	WIRE 8XLP UL3321 C-L POLYOLEFIN
6	1	XLP18 BLKW/YLW	WIRE 18XLP UL3321 C-L POLYOLEFIN
5	1	XLP18 BLKW/ORG	WIRE 18XLP UL3321 C-L POLYOLEFIN
4	A/R	PARKER O-LUBE	LUBRICANT BARIUM BASED
3	A/R	PAVE-Seal 150	EPOXY BLACK
2	1	-325 VITON	O-RING -325 VITON
1	1	0324	HOUSING SP26-E
ITEM	QTY.	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5
 X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005
 ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS

PAVE technology co. 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION PAVE-Seal® Cable Harnesses
 SP26-E-150-4/2-XLP8/18-12-24

PART NUMBER 2488

REVISION LEVEL A

PROJECTION